

Introducing the Autobag[®] PaceSetter PS 125[™] Tabletop Baggers The Ultimate in Hand Load Packaging Systems

The Autobag[®] PaceSetter PS 125[™] and PS 125 OneStep[™] Tabletop Baggers are specifically designed to bring simplicity, versatility, quality and value to hand load packaging applications.

Operating at speeds up to 25 bags per minute (15 BPM OneStep version), the PS 125 bagging systems offer innovative engineering in a simple, tabletop design. The PS 125 features a small footprint of 22 x 19 inches, and weighs just 82 pounds. The quiet, all-electric design does not require compressed air to run, making the unit highly adaptable in any low- to mid-volume production environment.

The PS 125 is simple to operate, with a user-friendly display that enables easy access to operating parameters, job set-up, job storage, and on-board system diagnostics. The unique, locking turntable combines with the AutoThread[™] feature to provide ergonomic handling and changeover of Autobag bags-on-a-roll. Bags are automatically indexed, loaded by hand, then sealed using the Push-to-Seal[™] function, a standard footswitch, or via automatic cycle control.

The PaceSetter PS 125 OneStep[™] includes the same conveniences of the standard PS 125 with the addition of a built-in PH 412 imprinter. Featuring next-bag-out printing technology that is ideal for short run and order fulfillment applications, the PS 125 OneStep is capable of printing high resolution graphics, text and bar codes directly on the bag, eliminating the need for a separate labeling operation.

The printer features a tilt-back print head for easy maintenance, and the optional AutoLabel™ label design software simplifies label creation. Using system-matched Autobag pre-opened bags-on-a-roll in sizes up to 10.5" wide and 17" long, the PaceSetter PS 125 and PS 125 OneStep offer a simple, and cost-effective packaging solution.

USER BENEFITS

- All-electric system does not require compressed air to run
- Compact design is ideal for low- to mid-volume packaging operations
- Locking turntable and AutoThread feature provide easy bag access and changeover
- Open loading area and controlled seal bar maximize loading flexibility and operator safety
- Automatic or manual operating modes for optimum flexibility and productivity
- Stores jobs for later recall using operator-friendly controls
- On-board system diagnostics simplify maintenance and maximize productivity
- Next-bag-out printing feature ensures greater accuracy and eliminates product queuing in order fulfillment applications*
- Capable of printing high resolution graphics, text and bar codes directly on the bag*
- Tilt-back printer head for easy maintenance*

*PS 125 OneStep version only

TYPICAL APPLICATIONS

- Automotive & appliance parts
- Hardware & DIY
- Electrical & electronic
- Plumbing & heating
- Hobby & craft

- Jewelry & novelty items
- Cosmetics & beauty aids
- Disposable health care
- Mail order fulfillment





STANDARD FEATURES

- Two configurations available: PS 125™ (without printer) or PS 125 OneStep™ (with printer)
- Small footprint, 22" x 19", frees up valuable tabletop space
- Locking turntable for ergonomic and rapid access to Autobag® bags-on-a-roll
- Operator-friendly control panel, bright VF display, and easy-to-navigate menu structure
- Stores up to 10 jobs in memory for rapid recall
- Automatic bag sealing and indexing, Push-to- Seal™ or standard footswitch operation
- AutoThread[™] feature for easy bag changeovers
- Multi-position bag support shelf for flexibility
- Dancer assembly for positive bag-web control provides accurate positioning for inline printing*, loading and sealing
- Multiple ports for enhanced printer communications: USB, Serial, Parallel and Ethernet*
- Tilt-back printer head for easy maintenance*

OPTIONS

- Bag deflators
- Simple funnels
- AutoLabel™ Designer software*
- Basic Spare Parts Kit
- *PS 125 OneStep version only

TECHNICAL SPECIFICATIONS

	PS 125	PS 125 OneStep
Weight:	82 lbs (37 kg)	110 lbs (50 kg)
Electrical:	110/220 VAC; 50/60 Hz; 5.0/2.7 Amps	110/220 VAC; 50/60 Hz; 5.0/2.7 Amps
Pass-Through:	Up to 3.4 in.	Up to 3.4 in.
Bag Thickness:	1.0 to 4.0 mil	1.0 to 4.0 mil
Bag Sizes:	W 2 to 10.5 in. L 4 to 17 in.	W 2 to 10.5 in. L 4 to 17 in.

Dimensions:



19 in. (48 cm) Depth



19 in. (48 cm) Depth

MECHANICAL FEATURES

Tilt-back printer* enables fast and easy maintenance and is system-matched for highest print quality using genuine AutoLabel™ Thermal Transfer Ribbon



Turntable design enables easy access to bags, while the AutoThread™ feature simplifies bag changeovers



Open load area and controlled seal bar maximize loading flexibility and operator safety



Configuration Options

footswitch which allows

Use the simple Push-

to- Seal™ mode or choose the standard

for handsfree bag

sealing.

