

BB-2 BOTTOM BELT CASE TAPER

EASTEY DELIVERS WHAT YOU NEED. . . TODAY

Eastey's BB-2 case taper is a cost-effective top and bottom case taper designed for large run case sealing. BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes.

INNOVATIVE TECHNOLOGY, PROVEN RELIABILITY

BB-2 offers the durability, versatility and reliability that you have come to rely on from Eastey. The system's unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient al ernatives to hand taping.

TRUE VERSATILITY FOR YOUR NEEDS

BB-2 offers fast and easy case changes with adjustable side rails and fl xibility ranging from 5" to infini e box length. BB-2 is also able to seal cases ranging from 6" to 21" in width, as well as 4" to 20.5" in depth. Adjustments can be made on the fly with easy han tighten knobs on a single mast design. BB-2's open design is also perfect for integration with ink jet printers where coding is required on boxes.

COST-EFFECTIVE CASE SEALING

BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes at a cost-effective price.

EASTEY

CASE TAPING AS EASY AS 1-2-3

BB-2 top and bottom tape heads are interchangeable and tip back for easy threading. No air is required to run the BB-2 taping system so it can be placed anywhere in the factory. A safe single mast allows clear access to all components and adjusts for a variety of case sizes. The use of Eastey's BB-2 case taping machine can be learned in minutes, avoiding breaks in production and downtime, saving your company money and increasing your ROI.

INDUSTRIAL STRENGTH OPERATION

A single drive motor and aggressive industrial strength drive belts make BB-2 a workhorse that will stand up to your toughest challenges. Each case taping machine is made from 12 gauge steel that withstands even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use.

THE RIGHT SOLUTION

Rugged design. Proven reliability. Simple operation. Your benefits go on and on. When it comes o industrial operation, rely on Eastey to provide the right solution for your case sealing needs.



BB-2

BB-2 BOTTOM BELT CASE TAPER











- 1. Top and bottom tape heads are interchangeable and tip back for easy threading
- 2. Industrial strength drive belts move boxes consistently through the taper
- 3. Adjustable side rails and tape head offer fast and easy case changes
- 4. Top and bottom tapeheads are identical and can be removed instantly without tools. Choose from two options.

BB-2 FEATURES BB-2 TAPING SPECIFICATIONS • Plug-in and go operation Sealer Type Bottom belt, top and bottom case sealer • Powder coated 12 gauge steel Machinery Makeup Industrial strength 12 gauge steel, powdered coated for durability Interchangeable top and bottom **Belt Speed** 60 feet/per minute tape cartridges Tape Speed 30 cases/per minute, depending on box size and operator efficienc • Adjustable side rails Casters Rugged wheels for transportation within plant Industrial strength drive belts Front and Rear Packing Solid tables bolt before and/or after taping system to allow for case packing • Safe single mast design Adjustable Side Rails Palm grip knobs offer quick and simple adjustments • Easy hand-tighten adjustments Standard adjustable legs for 22.25" to 35.25" conveyor heights Height Adjustment • No air required **BOX SPECIFICATIONS** Depth • Low maintenance Minimum Box Size 5″ 6″ 4″ • Simple integration with ink jet printers 21″ 20.5" Maximum Box Size Infini e Includes 2 pack tables and casters 2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" Tape Size wide tape Proven design requires no lubrication, tips back for simple tape Tape Cartridge threading, removable for maintenance and interchangeable with top or bottom cartridges Air Requirements None 110 VAC, 60Hz, 6A **Electrical Requirements BB-2 OPTIONAL ACCESSORIES**

3" Tape Head	Accepts 3" wide tape rolls
Top Squeezers	Designed to stabilize the box and push the top flaps ogether for easier taping



