

PNEUMATIC SEMI-AUTOMATIC L-SEALING SYSTEMS

EASTEY ESA Professional Series L-Sealers are the ultimate workhorse for your most abusive sealing applications.

MODELS

ESA2016TK, ESA2028TK, ESA2040TK, ESA2050TK, ESA2070TK, ESA2080TK, ESA20100TK, ESA3040TK, ESA3050TK, ESA3070TK, ESA3080TK, ESA30100TK, ESA4040TK, ESA4050TK, ESA4070TK, ESA4080TK, ESA40100TK, ESA050TK, ESA5070TK, ESA5080TK, ESA50100TK

DURABILITY THAT CAN'T BE MATCHED

EASTEY's Professional Series ESA L-Sealers provide top of the line features and the most robust L-Sealer design on the market today. Expertly welded from 1/4" cold rolled steel, EASTEY Professional ESA L-Sealers will withstand even the most abusive real world sealing applications. As a measure of strength, EASTEY L-Sealers weigh nearly twice as much as competitive models.



PROVEN RELIABILITY FOR YOUR NEEDS

Eastey L-Sealers are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC. Cast seal arms, pneumatic operation, stainless steel film clamps, and heavy-duty magnet clamping are just some of the features that provide the durability you have come to rely on from EASTEY. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.


STANDARD FEATURES

- Designed to seal most polyolefin, polyethylene, and PVC* shrink films
- All-welded main frame from 1/4" cold rolled steel
- Built-in drawer for tools or spare parts
- Seal head casting equipped with head return cylinder
- Stainless steel film clamps hold film in place while sealing
- Dual palm pneumatic seal head activation
- Hot knife seal systems available with mushroom (standard), pancake, or arrow inserts
- Dual locking magnet clamps apply even pressure across sealbar
- Adjustable dwell time for better seal control
- Solid state temperature control adjustable for a variety of films
- Adjustable product tray accommodates wide variety of product sizes
- Takeaway conveyor can be raised or lowered to center-seal product
- Automatic takeaway conveyor
- Heavy duty film cradle allows for easy changeovers and adjustments
- Adjustable pin perforator provides air evacuation
- Side seal size from 20" – 50"; front seal size from 16" – 100"
- Maximum film width up to 44"
- Maximum film roll OD up to 12"; 10" with power unwind
- Custom two-part epoxy finish resists scratching
- Heavy duty casters for transportation within plant
- Available in 110v, 220v, or optional 480v
- 60-80 psi air requirement
- Easy to use design requires minimal training and maintenance
- Made in the USA



MODEL NUMBER	SEAL DIMENSIONS		MACHINE DIMENSIONS			STANDARD POWER			WEIGHT	SHP WT.
	FRONT	SIDE	WIDTH	HEIGHT	LENGTH	VOLTS	AMPS	PHASE		
ESA2016TK	16" 41 cm	20" 51 cm	34" 86 cm	44" 112 cm	63" 160 cm	220/110	10/20	1	600 lbs 272 kg	700 lbs 317 kg
ESA2028TK	28" 71 cm	20" 51 cm	34" 86 cm	44" 112 cm	84" 213 cm	220/110	10/20	1	700lbs 317 kg	800 lbs 362 kg
ESA2040TK	40" 102 cm	20" 51 cm	34" 86 cm	44" 112 cm	106" 269 cm	220	15	1	800 lbs 362 kg	900 lbs 408 kg
ESA2050TK	50" 127 cm	20" 51 cm	34" 86 cm	44" 112 cm	126" 230 cm	220	20	1	900 lbs 362 kg	1000 lbs 452 kg
ESA2070TK	70" 178 cm	20" 51 cm	34" 86 cm	44" 112 cm	167" 424 cm	220	25	1	1300 lbs 589 kg	1400 lbs 635 kg
ESA2080TK	80" 203 cm	20" 51 cm	34" 86 cm	44" 112 cm	187" 474 cm	220	20	1	1500 lbs 680 kg	1600 lbs 725 kg
ESA20100TK	100" 254 cm	20" 51 cm	34" 86 cm	44" 112 cm	227" 577 cm	220	20	1	1900 lbs 861 kg	2000 lbs 907 kg
ESA3040TK	40" 102 cm	30" 76 cm	43" 109 cm	44" 112 cm	106" 269 cm	220	20	1	1200 lbs 544 kg	1300 lbs 591 kg
ESA3050TK	50" 127 cm	30" 76 cm	43" 109 cm	44" 112 cm	126" 320 cm	220	20	1	1300 lbs 591 kg	1400 lbs 637 kg
ESA3070TK	70" 177 cm	30" 76 cm	43" 109 cm	44" 112 cm	167" 424 cm	220	25	1	1600 lbs 728 kg	1700 lbs 774 kg
ESA3080TK	80" 203 cm	30" 76 cm	43" 109 cm	44" 112 cm	187" 474 cm	220	25	1	1800 lbs 819 kg	1900 lbs 861 kg
ESA30100TK	100" 254 cm	30" 76 cm	43" 109 cm	44" 112 cm	227" 577 cm	220	25	1	2100 lbs 956 kg	2200 lbs 997 kg
ESA4040TK*	40" 102 cm	40" 102 cm	53" 135 cm	44" 112 cm	106" 269 cm	220	20	1	1700 lbs 774 kg	1800 lbs 819 kg
ESA4050TK*	50" 127 cm	40" 102 cm	53" 135 cm	44" 112 cm	126" 320 cm	220	20	1	1900 lbs 861 kg	2000 lbs 907 kg
ESA4070TK*	70" 177 cm	40" 102 cm	53" 135 cm	44" 112 cm	167" 424 cm	220	25	1	2100 lbs 956 kg	2200 lbs 997 kg
ESA4080TK*	80" 203 cm	40" 102 cm	53" 135 cm	44" 112 cm	187" 474 cm	220	25	1	2300 lbs 1043 kg	2400 lbs 1092 kg
ESA40100TK*	100" 254cm	40" 102 cm	53" 135 cm	44" 112 cm	227" 577 cm	220	25	1	2600 lbs 1179 kg	2700 lbs 1229 kg
ESA5050TK*	50" 127 cm	50" 127cm	63" 160 cm	44" 112 cm	126" 320 cm	220	20	1	1900 lbs 861 kg	2000 lbs 907 kg
ESA5070TK*	70" 177cm	50" 127cm	63" 160 cm	44" 112 cm	167" 424 cm	220	25	1	2100 lbs 956 kg	2200 lbs 907 kg
ESA5080TK*	80" 203 cm	50" 127cm	63" 160 cm	44" 112 cm	187" 474 cm	220	25	1	2300 lbs 1043 kg	2400 lbs 1092 kg
ESA50100TK*	100" 254 cm	50" 127cm	63" 160 cm	44" 112 cm	227" 577 cm	220	25	1	2600 lbs 1179 kg	2700 lbs 1229 kg

All machines require a 60-80 psi air connection * Powered film unwind included

STANDARD FEATURES



OPTIONAL ACCESSORIES



- A **Power film unwind**
Allows free feeding of film increasing operator efficiency.
- B **Film Inverter**
Inverting head allows the film to come off the back of machine. This pre-opens the film and minimizes operator effort which in turn increases output.
- C **Hot Knife Inserts**
Hot knife inserts available in Mushroom, Pancake, or Arrow styles.
- D **Left Hand Models Available**
- E **DuoSeal Continuously Heated Seal Bar**
- F **Lower Conveyor**
- G **Customer Product Guides and/or Product Tray**