

High-performance shrink tunnel with four-way ring nozzle heating system.

The Compact 650 DD from Kalfass shrinks in an extremely energy-efficient manner, using only the required amount of energy for optimal product packaging results. This is accomplished using four individually adjustable heating zones with a continuously adjustable fan speed and 4-way frequency control. Ensuring careful use of the world's resources.

SPECIFICATIONS

Adjustable working height:	32" - 35"
Tunnel clearance width, height:	25"/4" or 8"
Length of the heated tunnel hood:	71"
Power supply:	208 - 480 Volt
Continuously adjustable temperature:	up to 190°C/375°F
Transport Speed:	15' - 120' Minute
Installed heating capacity:	4 x 4.5kW



A total of four separately controllable ring nozzle heating systems provide uniform heat transfer to the packaged product.

YOUR BENEFITS HIGHLIGHTED

- Perfect packaging results using constantly uniform heat energy transfer to the packaged goods, regardless of the position on the conveyor belt
- Ring nozzle heating technology with integrated air circulating system for efficient energy recovery
- High level of insulation and compact design ensure fast warm-up times
- Easy adjustment of basic parameters (temperature, air volume and package speed) using continuously adjustable controller
- Intelligent technology ensures constant temperature during operation. Energy-intensive temperature fluctuations are prevented
- Carefully selected components, easy to maintain, maintenance-free plastic mesh belt