

## Kallfass Logi Wrap 500 3D - horizontal bagging machine

This “super talent” uses a measurement grid to identify the product dimensions and adapts the film packaging automatically to fit the product. Thus, tailor-dimensioned film packaging is always ensured. Regardless of whether shipping or return packaging, display or protective packaging, individual or container packaging, from now on you only need one machine to package your entire product range. The Logi Wrap 500 3D!



### FEATURES

- Film bag with stable, durable side seals, completely sealed on all four sides
- Very small footprint. Easy to integrate into the product flow of any supply chain with a minimum of space requirements, or can be used as a stand-alone solution
- After packing cycle, the product is discharged from the machine
- Packs reliably varying product dimensions in random order
- Capacity speed of up to 2000 cycles per hour
- All usual trade films, such as polyolefin, polyethylene, poly lactide acid (PLA), unprinted, printed, transparent or colored (opaque) can be easily processed
- Easy integration of label printers and data connection

### SPECIFICATIONS

Dimensions: length x width x height	71" x 43" x 83
Transverse seal bar, length:	22" (24")
Seal Bar clearance height:	up to 8"
Product length, min:	5"
Packaging capacity, max:	2000 cycles/hour
Film, flat film:	up to 24"
Label printing / data connection:	optional