

Flexible, Dependable, and Ready to Take On Your Toughest Challenges

Our Flagship Model for Maximum Speed!

The Shanklin Model T-62/T-72H Shrink Tunnel is designed for maximum performance with high speed wrappers, solving a multitude of persistent wrapping challenges.

These tough, efficient machines feature a high speed dual-chamber tunnel for optimum shrink capacity, each with independently controllable temperature, air velocity, and flow. Your choice of varying tunnel passage dimensions ensures that there's a model just right for your application!

- **Versatile** – The most versatile shrink tunnel on the market! Shrinks difficult packages; adjusts easily to handle a variety of applications.
- **Proven Reliable** – Includes long-lasting finstrip heater elements, precision temperature control units, and rugged 3/4 hp blower motors.
- **Easy to Use** – Simply set the variable speed conveyor and adjustable air velocity and temperature controls, and go!



T-62




T-72H

SPECIFICATIONS FOR T-62/T-72H

Tunnel passage	10" high x 18" wide x 61" long	12" high x 22" wide x 84" long
Tunnel size	38" wide overall x 38" high above conveyor	38" wide overall x 38" high above conveyor
Conveyor height	29" minimum, 42" maximum	29" minimum, 42" maximum
Conveyor lengths	77", 93", 109" lengths stocked (109" is standard length)	100", 116", 132" lengths stocked (132" is standard length)
Conveyor speeds	Variable from 25 to 150 ft./min.	
Power*	230 volts, 3 phase, 64 amps, 14.8 KVA max.	
Blower motors	Two motors, 3/4 hp each motor	
Heaters	Multiple finstrip (encased element)	
Temperature controller	Precision indicating controller calibrated 50° to 500° F. Independent temperature control for each shrinking chamber.	
Controls	<ul style="list-style-type: none"> • Main power circuit breaker • Tunnel on/off switch • Conveyor start/stop switch • Conveyor variable speed control • Main and top air velocity controls 	
Safety features	<ul style="list-style-type: none"> • Motor overload protection • High temperature limit switches • Main power circuit breaker • Emergency stop switches 	
Available options	<ul style="list-style-type: none"> • Side air cascade plates with adjustable dampers • Volume control for bottom air • End viewing windows • Live or dead roller conveyor • Special package guides • Teflon conveyor belt • Composite link conveyor belt • "Poly kit" for use with LDPE • Casters 	

*Optional voltages, amperages and KVA specifications can be supplied upon request.
 Specifications on all machines subject to change without notice. Some photos may show accessories not part of the basic machine.

T-62/T-72H PLAN VIEW



THE PERFECT PARTNER

The Shanklin T-62 or T-72H Shrink Tunnel performs seamlessly with our High-Speed Wrappers for a total quality shrink packaging solution.



STAINLESS STEEL MODELS AVAILABLE