

Simple, Reliable, and Hard-Working for Superior Packages Every Time

The Shanklin Model T-7H Shrink Tunnel gives you the heavy-duty, continuous service your packaging production demands. Loaded with features and accessories, the highlight of the T-7H is a higher tunnel opening designed to easily accommodate those medium- to high-profile packages that can pose frustrating wrapping challenges. Easy access front-mounted control box comes standard on the T-7H, in left- or right-hand options.

Virtually Maintenance-Free – Thanks to straightforward, dependable design.

• Easy to Use – Set temperature, conveyor speed, velocity, and go!

• Flexible – Adjustable top air jet velocity ensures superior shrinks of unusual product.

• **Durable** – Features heavy-duty conveyor, stainless steel mesh belt, and variable speed DC drive.





Shanklin T-7H Shrink Tunnel

SPECIFICATIONS FOR T-7H

Tunnel passage	12" high x 22" wide x 42" long
Overall dimensions	Maximum 82" high x 34 1/2" wide x 74" long Optional 24" discharge, giving overall length of 90"
Conveyor height	28" minimum, 40" maximum
Conveyor speeds	Variable from 15 to 120 ft./min.
Blower motor	3/4 hp, single phase capacitor start
Heaters	Six finstrip (encased element)
Power*	230 volts, 57 amps, 1 phase, 13.1 KVA max. (6.6 KVA normal usage) 230 volts, 36 amps, 3 phase, 8.2 KVA max. (4.1 KVA normal usage)
Temperature Controller	Precision indicating controller Calibrated 50° to 500° F
Controls	 Main power fused disconnect Tunnel control switch Adjustable top air flow Main air velocity Conveyor variable speed Conveyor switch Volume control for bottom air Cascade plates for side air
Safety features	 Motor overload protection Emergency stops switches High temperature limit switch
Accessories	 "Poly kit" for use with LDPE Live/dead roller conveyor Composite link conveyor belt Casters Package guides End viewing windows

T-7H PLAN VIEW



THE PERFECT PARTNER

Partner your T-7H Shanklin Shrink Tunnel with a Shanklin F-1 Form-Fill-Seal Wrapper for a complete, dependable, quality shrink packaging solution.



STAINLESS STEEL MODELS AVAILABLE

*Optional voltages, amperages and KVA specifications can be supplied upon request.

Specifications on all machines subject to change without notice. Some photos may show accessories not part of the basic machine.